

400 Seventh Street, S.W. Washington, D.C. 20590

DOT-E 12062 (THIRD REVISION)

EXPIRATION DATE: April 30, 2002

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Vulcan Chemicals Birmingham, AL

(SEE APPENDIX A FOR LIST OF ADDITIONAL GRANTEES)

2. PURPOSE AND LIMITATION:

- a. This exemption authorizes the transportation in commerce of pentachlorophenol in a non-DOT specification, pneumatic hopper trailer. This exemption provides no relief from any Hazardous Materials Regulation (HMR) other than as specifically stated herein.
- b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.242(b) in that the use of a non-DOT specification packaging is authorized.
- 5. <u>BASIS</u>: This exemption is based on the application of Vulcan Chemicals dated May 2, 2000, submitted in accordance with § 107.109.
- 6. HAZARDOUS MATERIALS (49 CFR § 172.101):

| Proper Shipping Name/ Hazardous Materials Description | Hazard Class/ Division | Identi- fication Number | Packing Group |
|--|------------------------------|-------------------------------|------------------|
| Pentachlorophenol | 6.1 | UN3155 | II |

7. SAFETY CONTROL MEASURES:

- a. <u>PACKAGING</u> Packaging prescribed is an aluminum non-DOT specification, pneumatic hopper trailer as follows:
- (1) J&L Tank in accordance with specification number 575A. The trailer has a capacity of one thousand cubic feet.
- (2) The Heil Company, Model 1040 Super Jet Dry Bulk, with a capacity of 1040 cubic feet.

b. TESTING -

- (1) At time of manufacture Trailers must be hydrostatically tested in accordance with J&L Tank manufacturing procedure No. 550-0001, dated May 16, 1997 or § 180.407(g) (viii). Test pressure must be no less than 1.5 times the maximum operating pressure.
- (2) <u>In-service test and inspection</u> Trailers must be subject to the following tests and inspections:
 - a. External visual inspection must be conducted in accordance with § 180.407(d) with an inspection interval of 1 year.
 - b. Internal visual inspection must be conducted in accordance with § 180.407(e) with an inspection interval of 5 years.
 - c. Leakage testing must be conducted in accordance with § 180.407(h) utilizing a test pressure of 12 psi (80% of maximum operating pressure) with a test interval of 1 year.
 - d. If the tank meets any of the conditions specified in § 180.407(b), the tank must be tested and inspected prior to being returned to hazardous materials service.
- c. <u>OPERATIONAL CONTROLS</u> Prior to shipment, each grantee must ensure all filling openings and discharge pipes are closed and secured to ensure the trailer is siftproof. Discharge valves must be secured in the closed position prior to transport.

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this exemption who receives a package covered by this exemption may reoffer it for transportation provided no modifications or changes are made to the package and it is reoffered for transportation in conformance with this exemption and the HMR.
- b. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle.
- 10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each motor vehicle used to transport packages covered by this exemption.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by § 172.700 through § 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken

under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued at Washington, D.C.:

Robert A. McGuire

MAY 17 2000

(DATE)

Acting Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, Washington, DC 20590-0001, Attention: Docket Section, 202-366-5046.

PO: DBurger/sln

The following are hereby granted party status to this exemption based on their application(s) submitted in accordance with § 107.107 and § 107.109, as appropriate:

| Company Name | Application | Issue | Expiration |
|--|-------------|-------------|------------|
| City/State | Date | Date | Date |
| Wood Protection Products, Inc. Charlotte, NC | 5/18/00 | MAY 26 2000 | 4/30/2002 |

Acting Associate Administrator for

Hazardous Materials Safety